

Technical Data Sheet

Date of Issue 30/03/2020

Rev. 01_11/01/2021

9064

Printed Warning Duct Tape

**Product Description**

9064 Printed Warning Duct Tape, PE laminated synthetic cloth duct tape, coated with a semi-permanent synthetic rubber – resin solvent free adhesive. Thanks to its adhesive formulation, the tape ensures excellent bonding to multiple rough and smooth surfaces at low temperatures. The text "PLEASE KEEP A SAFE DISTANCE" is bolded and printed directly on the carrier to help increase social distancing awareness. For clean removal, long-term UV exposure not recommended.

Features

- Printed text to increase visual warning
- Easy tear
- Withstand any weather condition
- Good abrasion resistance
- Excellent conformability
- Excellent adhesion on smooth and rough surfaces
- Perfectly waterproof

Main Applications

- Jointing and sealing
- General repairing
- Warning-marking

Technical Data

| | Metric | Imperial Units | Test Method |
|--------------------------|----------------------|----------------------|---------------------|
| Total weight* | 153 g/m ² | 153 g/m ² | ISO 536 |
| Total thickness* | 165 µm | 6.5 mils | Internal |
| MD tensile strength* | 34 N/cm | 19.4 Lbs/in | AFERA 5004/PSTC 131 |
| MD elongation at break* | 20 % | 20 % | AFERA 5004/PSTC 131 |
| Adhesion to steel plate* | 8.0 N/cm | 73.1 oz/in | AFERA 5001/PSTC 101 |
| Service temperature | -10°C / 60°C | 14°F / 140°F | |

Backing material

PE laminated synthetic cloth

Type of adhesive

Synthetic rubber resin - solvent free

*Typical value

Available colourBlack/
Yellow**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.