

Technical Data Sheet

Date of Issue 27/02/2023

Rev. 01_12/02/2024

2025 Painter's WR Basic Masking tape

**Product Description**

Professional and DIY masking tape characterized by a regular crepe paper backing and a solvent borne rubber resin white adhesive. Suitable for all common water and solvent base paints mainly in indoor operations even in humid and moist conditions. Designed to offer high performance in masking and painting activities, this tape guarantees high conformability and holding power on both smooth and irregular surfaces (walls, baseboards, trims, wood and metal).
FSC® and PEFC certified masking tapes available on demand.

Features

- Medium adhesion
- Good holding power
- Clean removal in humid environments without breaking
- Good resistance to moisture thanks to water resistant backing
- Suitable for most common water and solvent base paints
- Indoor removal time: 5 Days

Main Applications

- DIY and Professional masking, painting and building operations (no UV exposure recommended)

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	80 g/m ²	80 g/m ²	ISO 536
Total thickness*	110 µm	4.3 mils	Internal
MD tensile strength*	37 N/cm	21.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	7 %	7 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	1.9 N/cm	17.4 oz/in	AFERA 5001/PSTC 101
Service temperature	up to 55°C	up to 131°F	

Backing material

Saturated crepe paper

Type of adhesive

Natural rubber

*Typical value

Available colour

White Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.