

Technical Data Sheet

Date of Issue 06/12/2023

Rev. 01_20/12/2023

9056

Universal Grade Duct Tape

**Product Description**

Universal Grade, PE laminated synthetic cloth duct tape, coated with synthetic rubber – resin solvent free adhesive. Characterized by excellent conformability and tensile strength, it is designed for general-purpose use, making it suitable for a variety of DIY and contractor applications.

It offers good adhesive strength, durability, and flexibility. It is also resistant to moisture and can adhere well to a variety of surfaces, enabling this tape to become a perfect value for money and reliable and versatile duct tape.

UV exposure not recommended.

Features

- Easy tear
- Excellent adhesion on PE
- Low temperature resistance
- Excellent conformability
- Suitable for multiple surfaces
- Perfectly waterproof

Main Applications

- Bundling, sealing, temporary repairing operations
- Double glazing unit sealing
- General repair and protection in construction sites
- Jointing and sealing asbestos abatement and agriculture

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	131 g/m ²	131 g/m ²	ISO 536
Total thickness*	155 µm	6.1 mils	Internal
MD tensile strength*	35.0 N/cm	20.0 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	9.0 N/cm	82.2 oz/in	AFERA 5001/PSTC 101

Backing material

PE laminated synthetic cloth

Type of adhesive

Synthetic rubber resin - solvent free

*Typical value

Available colour**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.