

Technical Data Sheet

Date of Issue 28/05/2025

Rev. 00_28/05/2025

Scrim

Fiberglass Scrim Tape

**Product Description**

Scrim is a high quality scrim tape made of fiberglass and coated with adhesive glue on one side. It is used on the plasterboard gap to strengthen the strength of the wall.

This product is the perfect tool for any plasterboarding project, joining your boards and providing a smooth finish.

The mesh of the tape allows it to contain the jointing compound during plastering, creating a strong joint and the holes between the threads allow the plaster to cover all areas for a seamless finish when skimmed. In fact, the threads act as a reinforcing mesh and stop the joints from cracking as the adjacent plasterboard panels move with expansion, contraction and human action.

Features

- Self-adhesive and can be re-positioned
- Eliminates need for pre-plastering
- Extra reinforcement when joining plasterboards
- Eliminates blisters and bubbles

Main Applications

- For joint finishing, crack and hole repair
- For drywall and plaster walls and ceilings

Technical Data

	Value	Test Method
Total Weight	65 g/m ²	ISO 536
Tensile strength warp	> 120 N/cm	AFERA 5004/PSTC 131
Tensile strength weft	> 140 N/cm	AFERA 5004/PSTC 131

Backing material

Fiberglass

Type of adhesive

Acrylic

Available colour

White

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.