

**Technical Data Sheet**

Date of Issue 11/10/2016

Rev. 00\_02/03/2023

# 5020

## Painter's Low Tack Fine Line Masking Tape

The mark of  
responsible forestry**Product Description**

Professional high-performance low tack masking tape designed to ensure extremely smooth, clean and sharp paint edges while protecting freshly painted surfaces. It is produced with a Japanese washi paper backing and a gently acrylic adhesive that requires a very low removal force.

PPM Masking Tape 5020 is the ideal product for touch-ups and finishes on freshly paints applied on smooth surfaces, assuring easy and clean removal without leaving residues within 24 hours from the application. FSC® certified masking tapes available on demand.

**Features**

- Japanese Washi Paper
- Low adhesion
- Sharp paint break-lines
- Resistant to moisture and most common water and solvent base paints
- 7 days indoor clean removal
- 24 hours clear removal on freshly painted surfaces\*\*
- Excellent paint anchorage

**Main Applications**

- Touch-ups and finishes on fresh painted surfaces
- Fine line on smooth surfaces

\*\*Please check the drying time of the paint you are using before removing the tape or applying the second coat of paint.

**Technical Data**

	Metric	Imperial Units	Test Method
Total weight*	72 g/m <sup>2</sup>	72 g/m <sup>2</sup>	ISO 536
Total thickness*	80 µm	3.1 mils	Internal Method
MD tensile strength*	30 N/cm	17.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	3.5 %	3.5 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	1.2 N/cm	11 oz/in	AFERA 5001/PSTC 101

**Backing material**

Washi paper

**Type of adhesive**

Water base acrylic

\*Typical value

**Available colour**

Violet

**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

**Storage and Shelf Life**

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.