

**Technical Data Sheet**

Date of Issue 28/09/2023

Rev. 03\_10/01/2024

# 2810

## Blue Painter's Tape



The mark of responsible forestry

**Product Description**

Professional masking tape characterized by a robust crepe paper backing and a solvent-borne rubber resin adhesive, meticulously designed for masking operations on various surfaces, including smooth or lightly textured walls, trim, baseboards, tile, and glass. With good mechanical strength and high conformability, PPM 2810 ensures precise and clean results in painting projects, whether indoors or outdoors. It boasts UV resistance and guarantees residue-free removal for a period of up to 14 days. This extended clean removal period makes it suitable for both short touch-ups and long-term masking needs. FSC® certified masking tapes available on demand.

**Features**

- High conformability
- 14 days UV resistance with clean removal (not painted)
- Good paint anchorage
- Resistant to moisture and most common water and solvent base paints

**Main Applications**

- Outdoor/Indoor professional masking for painting operations in Painting and Building sector.

**Technical Data**

	Metric	Imperial Units	Test Method
Total weight*	99 g/m <sup>2</sup>	99 g/m <sup>2</sup>	ISO 536
Total thickness*	150 µm	5.9 mils	Internal
MD tensile strength*	38 N/cm	21.7 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	2.3 N/cm	21.0 oz/in	AFERA 5001/PSTC 101

**Backing material**

Saturated crepe paper

**Type of adhesive**

Natural rubber

\*Typical value

**Available colour**

Blue

**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

**Storage and Shelf Life**

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.