

Technical Data Sheet

Date of Issue 06/06/2016

Rev. 00_06/06/2016

276
Easy Protection
PVC Tape



Product Description

Easy Protection PVC Tape is a matte finish PVC tape characterized by an easy unwinding, straight tearability and a clean removal without residue.

It is suitable for protection of surfaces during plastering and rendering operations, protection of windows frames and ceramic bathroom furnitures and jointing plastic protection boards in the construction industry.

Features

- Hand Tearable
- Clean Removal
- Easy Unwind
- Matte Finish

Main Applications

- Protection of Surfaces during renovation
- Protection of Window Frames
- Jointing of plastic protection board in construction industry
- Easily torn for patching, retaining, and temporary protection on site

Technical Data

	Units	Std. Values
Total Thickness	µm	150
MD tensile strength	N/cm	20
MD elongation at break	%	100
Peel Adhesion	N/cm	1.5
Service Temperature (up to)	°C	70

Backing material
PVC

Type of adhesive
Natural Rubber (Solvent Borne)

Available colour



Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.