

Technical Data Sheet

Date of Issue 29/04/2020

Rev. 09_12/02/2024

5110

Painter's Indoor Fine Line Masking Tape

The mark of
responsible forestry**Product Description**

Professional high-performance Washi Masking Tape designed to be the all-in-one product for every painting and decorating activities in indoor environments. Thanks to its special tacky rubber-based adhesive, the Washi Tape 5110 ensures absolutely clean, razor sharp paint edges from most common indoor surfaces with absolute clean removal without damages after 1 week from the application. It is very conformable, compatible with both solvent-based and water-based paints, and water resistant, becoming the universal product for every indoor painting activity where professional result is requested. UV exposure not recommended. FSC® certified masking tapes available on demand.

Features

- Tacky special adhesive with delicate but firm quick stick
- Soft and stable unwinding
- Sharp paint break-lines
- Resistant to moisture and most common water and solvent base paints
- 1-week clean removal from most common surfaces in indoor environment (PVC, glass, wood, aluminum, drywalls)
- 4 days clean removal from delicate surfaces in indoor environment like fresh paints**
- Excellent paint anchorage
- Water resistant

Main Applications

- Fine line painting application for indoor and decorative jobs

**Please check the drying time of the paint you are using before removing the tape or applying the second coat of paint.

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	67 g/m ²	67 g/m ²	ISO 536
Total thickness*	82 µm	3.2 mils	Internal
MD tensile strength*	30 N/cm	17.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	3.5 %	3.5 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	1.5 N/cm	13,7 oz/in	AFERA 5001/PSTC 101

Backing material

Washi paper

Type of adhesive

Natural rubber

*Typical value

Available colour

Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.