


Technical Data Sheet

Date of Issue 11/10/2016

Rev. 03_11/01/2021

8050

Carpet Double-Sided Film Tape

**Product Description**

Carpet high - adhesion double-sided film tape characterized by a OPP carrier, a siliconized paper liner and a synthetic rubber resin solvent free adhesive. Hand tearable, easy to use and stretchable for curved surfaces, it is suitable for flooring and carpeting, for mounting and attaching in trade show and entertainment industry.

Features

- High adhesion
- Good holding power
- Hand tearable
- Excellent contact on smooth and rough surfaces
- Excellent conformability

Main Applications

- Flooring
- Carpet fixing
- Light-medium weight material mounting

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	110 g/m ²	110 g/m ²	ISO 536
Total thickness*	115 µm	4.5 mils	Internal
MD tensile strength*	27 N/cm	15.4 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	620 %	620 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	6.5 N/cm	59.4 oz/in	AFERA 5001/PSTC 101

Carrier

50my non oriented
clear polypropylene

Liner

80 gr/sqm two sides
siliconized paper

Type of adhesive

Synthetic rubber resin - solvent free

*Typical value

Available colour

Brown Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.