

Technical Data Sheet

Date of Issue 17/11/2020

Rev. 08_14/06/2021

5025

Painter's Ultra Delicate Masking Tape

**Product Description**

Painter's Ultra Delicate Masking Tape designed to ensure professional finish even on the most sensitive surfaces, where any other product would cause damages.

Its ultra-sensitive adhesive is designed to prevent bleed through on semi-rough surfaces as plaster walls and extremely delicate surfaces as fresh paint and wallpapers to ensure a clean and gentle removal up to 1 week after the application.

PPM Masking Tape 5025 is the ideal product for indoor masking operations on common indoor surfaces up to 14 days without damaging the surface on removal. It can be precisely and reliably applied on door profiles and windows outlines exposed to UV rays up to 1 week.

Features

- Japanese Washi Paper
- Special ultra-delicate adhesive formula
- Sharp paint break-lines
- Resistant to moisture and most common water and solvent base paints
- Clean removal up to 1 week on extremely delicate surfaces (plaster, wallpapers, fresh paint)**
- Clean removal up to 2 weeks on common indoor surfaces (PVC, Glass, Wood, Aluminium)
- Excellent paint anchorage

Main Applications

- Touch-ups and finishes on fresh painted or ultra-delicate areas
- Fine Line painting indoor applications

**Please check the drying time of the paint you are using before removing the tape or applying the second coat of paint.

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	64 g/m ²	64 g/m ²	ISO 536
Total thickness*	75 µm	3.0 mils	Internal Method
MD tensile strength*	30 N/cm	17.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	3.5 %	3.5 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	0.45 N/cm	4.1 oz/in	AFERA 5001/PSTC 101

Backing material

Washi paper

Type of adhesive

Water base acrylic

*Typical value

Available colour

Pink

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.